SPECIFICATIONS FOR MAGNAGLIDE TM AIR POWERED OPENER

Operator Type

1. MagnaGlide TM Air Powered Opener

- A. 2" Stainless Steel Tube
- B. Chainless Direct Drive
- C. 1/4" NPT x 3/8" Poly Airline Fittings
- D. Stainless Steel Brackets and Fasteners
- E. Magnetic Coupled Piston to Drawbar Cylinder
- F. Sealed Stainless Steel Shock Absorbing Cylinder
- G. Three Year Unlimited Warranty
- H. Wiper Seal built into Carriage to prevent dust accumulation

2. Control Box Consisting of the Following

- A. Automatic Valve- lifetime warranty on coils
- B. 24 VAC Circuitry
- C. Ten Place Terminal Strip for easy electrical hookup
- D. Nema 4 up/down buttons on cover
- E. Fused Circuitry
- F. Valve mounted with Gasket, not O-Rings
- G. Nema 4 Rated Fiberglass Box
- H. Noise Mufflers
- I. Electric Eye Pin Sockets are pre-wired

Recommended Upgrades

- A. Emergency Open Button-opens the door in case of power failure
- B. Automatic Oilier-performs controlled oil drops into airlines
- C. Inline Airline Dryer-eliminates excess water and buildup from your compressor